



Highlights

- ▶ Contact free and real time
- ▶ Accurate measurement
- ▶ For high resistive metal filaments
- ▶ For high value conductive fibers
- ▶ Up to 200 sensors
- ▶ Single-lane and multi-lane solutions
- ▶ High production speed up to 10 m/s
- ▶ Feed data directly to a PLC

Applications

- ▶ Surface resistivity (Ohm/sq)
- ▶ Electrical resistivity (Ohm/m)
- ▶ Metal substrate thickness (μm)
- ▶ Defects monitoring

Parameters

- ▶ Conductive fiber uniformity
- ▶ Filament breakedge & fuzz
- ▶ Tow twist & splice
- ▶ Coating resistivity
- ▶ Conductive coating uniformity
- ▶ Impregnation dry/ wet
- ▶ Degree of metalization
- ▶ Fiber spreading
- ▶ Filament winding

Materials

- ▶ Coated yarn
- ▶ Metal fibers
- ▶ Conductive coating
- ▶ Nanowire (CNT, AgNW)
- ▶ Carbon fiber
- ▶ Smart textiles
- ▶ Shielding and EMI materials

SURAGUS GmbH
Maria-Reiche-Straße 1
01109 Dresden
Germany

+49 351/32 111 520
info@suragus.com

www.suragus.com
www.sheet-resistance-testing.com
www.suragus.com/FAQ
www.suragus.com/inline-WT

Made and Engineered in Germany

Innovation Award by
Free State of Saxony 2013
1st Place





Parts geometry	Width: 1 - 20 mm Height: 5 mm
Sensor size	1 - 20 mm
Sensor type	Open / Closed loop
Measuring	Resistivity (Ohm/m) Sheet resistance (Ohm/sq) Shielding quality Coating uniformity
Measurement range	Resistivity 0.5 mOhm/m - 500 Ohm/m Surface resistivity 0.001 Ohm/sq - 250 Ohm/sq
Speed	1 - 10.000 measurements per second
Mode	Non-contact
Method	Inductive and capacitive
Add-ons	Scalable to multiple lines Optical camera
Device size (w/h/d)	Standard 80 x 60 x 70 mm Customized to integration position

Software - EddyCus® TF inline Series

- ▶ Several views and user level
- ▶ Live view with upper and lower limits and alarm functions
- ▶ Analysis view providing statistics
- ▶ Can handle data of several thousands measurements per second
- ▶ Data storage into SQL database
- ▶ Customizable automatic data export (csv, txt, xls,...)
- ▶ Several smart functions (automated DB cleaning, self-reference etc.)
- ▶ Parameterizable I/O modules (triggering of actions or alarms)

